



**Flexbar Machine Corporation  
Material Safety Data Sheet**

**533896**

<b>1. Product and Company Identification</b>	
Product Name <b>FLEXBAR Reprorubber® Thin Pour Material</b>	MSDS Code Number <b>533896</b>
Trade Name & Synonyms <b>FLEXBAR Reprorubber® Thin Pour Material</b>	Date of Last Revision <b>11/23/12</b>
Chemical Name <b>Vinyl Polysiloxane</b>	Manufacturer <b>Flexbar Machine Corporation</b>
C.A.S. Number <b>N. A.</b>	Address <b>250 Gibbs Road Islandia NY 11749-2697 <a href="http://www.flexbar.com">http://www.flexbar.com</a></b>
Grades or Minor Variant Identities <b>N. A.</b>	Information Telephone Number <b>(631) 582-8440</b>
Product Use (for Canada) <b>N. A.</b>	Emergency Telephone Number <b>(800) 879-7575</b>

<b>2. Composition Of Ingredients – Base Paste</b>			
<b>Hazardous Components</b>	<b>C.A.S. Number</b>	<b>Exposure Limits</b>	<b>%</b>
Silicon Dioxide - Amorphous	7631-86-9	1.2 mg/M <sup>3</sup>	5 – 10
Silicon Dioxide -Crystalline	14464-46-1	0.05 mg/M <sup>3</sup>	15 – 20
<b>Non - Hazardous Components</b>			
Vinyl dimethyl polydimethylsiloxane	68083-19-2	N. E.	65 - 70
Polymethylhydrogen siloxane	68037-59-2	N. E.	8 – 15
FD & C Blue # 1	3844-45-9	N. E.	< than 1

<b>2. Composition Of Ingredients – Catalyst Paste</b>			
<b>Hazardous Components</b>	<b>C.A.S. Number</b>	<b>Exposure Limits</b>	<b>%</b>
Silicon Dioxide - Amorphous	7631-86-9	1.2 mg/M <sup>3</sup>	5 – 10
Silicon Dioxide -Crystalline	14464-46-1	0.05 mg/M <sup>3</sup>	15 – 20
<b>Non - Hazardous Components</b>			
Vinyl dimethyl polydimethylsiloxane	68083-19-2	N. E.	65 - 70
Yellow Fluorescent organic dye	39277-28-6	N. E.	< than 2
Organo Platinum complex	68478-92-2	N. E.	< than 1

<b>3. Hazard Identification</b>					
<b>Emergency Overview: Material may be mildly irritating to eyes.</b>					
Routes of Exposure	Signs and Symptoms	Single, Repeated, or Lifetime Exposure	Severity (Mild, Moderate, Severe)	Acute and Chronic Health Effect(s)	Target Organ(s)
Eye	Material can cause irritation.	Single	Moderate	Irritation and possible corneal damage	N. A.
Skin	Material may be an irritant	Single & Repeated	Moderate	Irritation or possible allergic response.	N. A.
Inhalation	N. A.	N. A.	N. A.	N. A.	N. A.
Ingestion	Material is probably not harmful if swallowed	N. A.	Mild	Low order of toxicity is expected when large amounts of material are ingested. Acute toxicology study in rats LD <sub>50</sub> >2,000 mg/kg.	N. A.
Other	N. A.	N. A.	N. A.	N. A.	N. A.
Medical Conditions Aggravated by Exposure Open sores and wounds of the skin.					
Carcinogenicity NTP?: Not listed IARC monographs?: Not listed OSHA regulated?: No All components of this product are in compliance with the inventory listing Requirements of the U. S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.					
Potential Environmental Effects Do not allow to enter sewers/ surface or ground water.					
NFPA Hazard Classification Ratings (Scale 0-4), Health = 0, Fire = 1, Reactivity = 0					



## Flexbar Machine Corporation Material Safety Data Sheet

<b>4. First Aid Measures</b>			
Routes of Exposure	First Aid Instructions	Immediate Medical Attention	Delayed Effects
Eye	Rinse opened eye for several minutes under running water. If symptoms persist consult physician	N. A.	N. A.
Skin	Immediately wash with soap and water and rinse thoroughly	N. A.	N. A.
Inhalation	Supply fresh air, consult physician if symptoms persist	N. A.	
Ingestion	If symptoms persist consult physician	N. A.	Low order of toxicity is expected when large amounts of material are ingested. Acute toxicology study in rats LD <sub>50</sub> >2,000mg/kg.
Other	N. A.	N. A.	N. A.
Note to Physicians (Treating, Testing and Monitoring): Treat symptomatically.			

<b>5. Fire and Explosion Data</b>			
Flashpoint Method: N. A.	Flammable (Explosive) Limits in Air LEL: N. A. UEL: N. A.	Autoignition Temperature: N. A. Product will not autoignite.	Other: N. A.
Flame Propagation or Burning Rate (for Solids) N. A.	Properties Contributing to Fire Intensity: N. A.	Flammability Classification: N. A.	
Extinguishing Media: CO <sub>2</sub> , extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire-extinguishing methods suitable to surrounding areas.		Extinguishing Media to Avoid: Water with full jet.	
Protection and Procedures for Firefighters: Firefighters should wear self-contained respiratory protective devices.			
Unusual Fire and Explosion Hazards: No dangerous decomposition products known. -Product does not present an explosion hazard.			

<b>6. Accidental Release Measures</b>
Containment Techniques: Material is a high viscosity paste and as such will not flow.
Spill/Leak Clean-up Procedures and Equipment: Wear protective clothing and scoop up bulk material and place in a labeled plastic or metal container. Avoid gross skin contact to minimize the possibility of contact dermatitis to susceptible persons. Ensure adequate ventilation.
Evacuation Procedures: N. A.
Special Instructions: N. A.
Reporting Requirements: N. A.

<b>7. Handling and Storage</b>
Handling Practices and Warnings: Handling of this product should be by trained users only. Observe normal care for working with chemicals.
Storage Practices and Warnings: Store only in the original package. Keep package tightly sealed. Store in a dry area. Protect from exposure to direct light. Store away from food and beverages.

<b>8. Exposure Control / Personal Protection</b>		
Ventilation: None required during normal intended use of this product	Other Engineering Controls: N. A.	
Routes of Entry	Personal Protective Equipment (PPE) for Normal Use	PPE for Emergencies
Eye/Face	Safety Glasses	N. A.
Skin	The glove material has to be impermeable and resistant to the product.	N. A.
Inhalation	Not Required	N. A.
Body Protection	Protective work clothing	N. A.
General Hygiene Considerations and Work Practices: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at end of work. Avoid contact with the eyes and skin. Do not eat, drink or smoke when using.		
Protective Measures During Repair and Maintenance of Contaminated Equipment: N. A.		
Other Protective Measures and Equipment: N. A.		

<b>9. Physical and Chemical Characteristics</b>		
Appearance: Blue colored runny paste. Catalyst is yellow runny paste.	Odor: Faint sweet odor.	
Normal Physical State: Material is low viscosity liquid. (Runny paste).	Melting Point: N. A.	
Specific Gravity: Varies from 1.1 g/cm <sup>3</sup>	Solubility in Water: Not soluble	pH: N. A.
Vapor Pressure (mm Hg): N. A.	Vapor Density (AIR=1) N. A.	Evaporation Rate (Butyl Acetate =1) N. A.
Other: N. A.		



**Flexbar Machine Corporation  
Material Safety Data Sheet**

<b>10. Stability and Reactivity Data</b>	
Incompatibility (Materials to Avoid): Strong Oxidizing materials.	
Hazardous Products Produced During Decomposition: No dangerous decomposition products known if used according to Directions for Use.	
Hazardous Polymerization: <input type="checkbox"/> May Occur <input checked="" type="checkbox"/> May Not Occur	Conditions to Avoid: None known
Stability? <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable	Conditions to Avoid: None known

<b>11. Toxicological Information</b>
Toxicity Data, Epidemiology Studies, Carcinogenicity, Neurological Effects, Genetic Effects, Reproductive Effects, or Structure Activity Data: Product may irritate the skin and mucous membranes. The unpolymerized product may cause irritation to the skin in susceptible persons. On the eye the product has an irritating effect. Sensitization: No sensitizing effects known.

<b>12. Ecological Information</b>
Toxicity Data, Environmental Fate, Physical/Chemical Data, or other Data Supporting Environmental Hazard Statements: Water Hazard class I (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water streams or sewage system.

<b>13. Disposal Considerations</b>
Regulations: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Dispose of material as solid waste in a closed container. Dispose of in accordance with Federal, State and Local regulations
Properties (Physical/Chemical) Affecting Disposal: Dispose of material as solid waste in a closed container.

<b>14. Transport Information</b>	
Regulated for Shipping: No. Not Regulated	DOT Shipping Name: Not Regulated

<b>15. Regulatory Information</b>
U.S. Federal Regulations: <u>CERCLA 103 Reportable Quantity</u> : This product is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations
Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None
Section 302 Extremely Hazardous Substances (TPQ): None
EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.
U.S. State Regulations California Proposition 65: This product does not contain any chemicals, which are on the California Proposition 65 list.
Other: N. A.

<b>16. Other Information</b>
To the best of our knowledge this product does not contain gluten, wheat grains, flaxseed, natural rubber, or natural latex. All components are synthetically produced; none are derived from animal products.

**FLEXBAR MACHINE CORPORATION**  
250 GIBBS ROAD  
ISLANDIA, NY 11749  
800-879-7575 • FAX 631-582-8487  
[www.flexbar.com](http://www.flexbar.com)  
sales@flexbar.com